

230V Gearmotor

Max. leaf weight

900 Kg

Max speed

12 m/min.

Use frequency

40%

safe



- Easy programming thanks to the display and to the prewired control unit
- · Magnetic limit switch.
- Integrated encoder with reverse function upon obstacle detection and specific management in opening and slow down



DIMENSIONS AND TECHNICAL SPECIFICATIONS		
Model	741 E Z16 with encoder	
Power supply voltage	220-240V~ 50/60 Hz	
Motor	Single phase	
Max. power	500 W	
Max. torque	24 Nm (*)	
Max expressed force	650 N (*)	
Reduction ratio	1:25	
Max. leaf width	15 m	
Leaf speed	12 m/min	
Speed adjustment and motor control	No	
Opening and closing limit switch	Magnetic	
Pinion	Z16 module 4	
Encoder	Optical encoder	
Force adjustment	Via electronic control board	
Operating ambient temperature	-20°C ÷ +55°C	
Thermal protection	140°C	
Protection class	IP44	
Weight	11 Kg	
Dimensions (LxDxH)	295 x 221 x 322 mm	
Max. leaf weight	900 Kg	
Use frequency	S3 - 40%	
Electronic equipment	740D incorporated	

(*) data referred to 230V~ 50Hz.



FAMILY MODELS

Model	Item code	
741 E Z16 with encoder	1097815	

PACKS

741 includes: an electromechanical gearmotor with 740D control unit, encoder for anti-crushing safety device, pinion for rack, two release keys, foundation plate, limit switch magnets.

Typical Installation Examples page. 341

ELECTRONIC CONTROL UNITS



740D (incorporated in automation) Info at page 150

RACKS



Galvanised rack 30x12 mod. 4 including weldon fittings (4 pcs pack, 1 m each)

490122



Galvanised rack 30x8 mod. 4 including weldon fittings (4 pcs pack, 1 m each)

490123



Galvanised rack 30x12 mod. 4 including mechanical fittings (4 pcs pack, 1 m each)

490124



Galvanised rack 30x12 mod. 4 including mechanical fittings (4 pcs pack, 1 m each) 490125



Discontinuing Reinforced nylon rack with steel core 30x20 and fixing accessories (4 pcs pack, 1 m each)

4901204



30x20 mod.4 nylon rack (4-pack of 1m pieces)


490333



Kit of 16 fastening screws (to use with cod.490333)

390178

INSTALLATION DIMENSIONS (MM)



NOTE

Max gate weight: 400kg.



Key operated buttons page 176

Safety devices page 190

Transmitters and receivers page 168

Photocells and columns page 186

Flashing lights page 198

Various accessories page 200